

HYTORC

TOOL MODEL: VERSA-4 W SLIM HEX LINK (LINK SIZES #7-10)
PRESSURE/TORQUE CONVERSION CHART FOR HEX SIZES 2 9/16" TO 3 1/2"

Standard Torque Chart

PRESSURE IN PSI	TORQUE IN			PRESSURE IN BAR
	FT. LBS.	KGM	NM	
1500	740	102	1003	104
1600	791	109	1072	110
1800	893	124	1211	124
2000	996	138	1350	138
2200	1098	152	1488	152
2400	1200	166	1627	165
2600	1302	180	1765	179
2800	1404	194	1904	193
3000	1507	208	2042	207
3200	1609	223	2182	220
3400	1712	237	2321	234
3600	1815	251	2460	248
3800	1918	265	2600	262
4000	2020	279	2739	276
4200	2124	294	2879	290
4400	2227	308	3019	303
4600	2331	322	3159	317
4800	2434	337	3300	331
5000	2537	351	3440	345
5200	2641	365	3580	358
5400	2744	379	3720	372
5600	2847	394	3860	386
5800	2950	408	3999	400
6000	3054	422	4139	414
6200	3157	437	4279	427
6400	3260	451	4420	441
6600	3364	465	4560	455
6800	3467	479	4700	468
7000	3570	494	4840	482
7200	3672	508	4978	496
7400	3774	522	5116	510
7600	3876	536	5255	524
7800	3978	550	5393	538
8000	4080	564	5531	552
8200	4183	579	5671	565
8400	4286	593	5810	579
8600	4389	607	5950	593
8800	4492	621	6089	607
9000	4595	635	6229	620
9200	4696	649	6366	634
9400	4798	664	6504	648
9600	4899	678	6641	662
9800	5000	692	6778	676
10000	5101	706	6916	690