

HYTORC

TOOL MODEL: VERSA-4 W SLIM HEX LINK (LINK SIZES #3-6)
PRESSURE/TORQUE CONVERSION CHART FOR HEX SIZES UP TO 2 3/8"

Standard Torque Chart

PRESSURE IN PSI	TORQUE IN			PRESSURE IN BAR
	FT. LBS.	KGM	NM	
1500	661	91	896	104
1600	706	98	957	110
1800	796	110	1079	124
2000	886	123	1201	138
2200	976	135	1324	152
2400	1067	148	1446	165
2600	1157	160	1569	179
2800	1248	173	1692	193
3000	1338	185	1814	207
3200	1429	198	1937	220
3400	1520	210	2061	234
3600	1611	223	2184	248
3800	1702	235	2307	262
4000	1793	248	2430	276
4200	1883	260	2553	290
4400	1974	273	2676	303
4600	2064	285	2798	317
4800	2155	298	2921	331
5000	2245	311	3044	345
5200	2335	323	3166	358
5400	2425	335	3288	372
5600	2515	348	3410	386
5800	2605	360	3532	400
6000	2695	373	3654	414
6200	2785	385	3775	427
6400	2874	398	3897	441
6600	2964	410	4018	455
6800	3054	422	4139	468
7000	3143	435	4261	482
7200	3234	447	4384	496
7400	3324	460	4507	510
7600	3415	472	4630	524
7800	3506	485	4753	538
8000	3597	497	4875	552
8200	3683	509	4993	565
8400	3770	521	5111	579
8600	3857	533	5228	593
8800	3943	545	5346	607
9000	4030	557	5463	620
9200	4118	570	5582	634
9400	4206	582	5701	648
9600	4294	594	5820	662
9800	4382	606	5940	676
10000	4469	618	6059	690