

HYTORC

TOOL MODEL: VERSA-8 W SLIM HEX LINK (LINK SIZES #4-9)
PRESSURE/TORQUE CONVERSION CHART FOR HEX SIZES 2 7/16" TO 3 1/2"

Standard Torque Chart

PRESSURE IN PSI	TORQUE IN			PRESSURE IN BAR
	FT. LBS.	KGM	NM	
1500	1457	201	1975	104
1600	1564	216	2121	110
1800	1779	246	2412	124
2000	1994	276	2703	138
2200	2187	303	2965	152
2400	2381	329	3227	165
2600	2574	356	3489	179
2800	2767	383	3751	193
3000	2960	409	4013	207
3200	3178	439	4308	220
3400	3395	470	4603	234
3600	3613	500	4898	248
3800	3830	530	5192	262
4000	4048	560	5487	276
4200	4235	586	5741	290
4400	4422	612	5995	303
4600	4610	638	6249	317
4800	4797	663	6503	331
5000	4984	689	6757	345
5200	5184	717	7027	358
5400	5383	744	7297	372
5600	5582	772	7567	386
5800	5781	800	7837	400
6000	5980	827	8107	414
6200	6181	855	8378	427
6400	6381	882	8650	441
6600	6581	910	8921	455
6800	6781	938	9192	468
7000	6981	965	9463	482
7200	7179	993	9731	496
7400	7376	1020	9999	510
7600	7574	1047	10267	524
7800	7772	1075	10535	538
8000	7970	1102	10803	552
8200	8169	1130	11074	565
8400	8369	1157	11345	579
8600	8568	1185	11615	593
8800	8768	1213	11886	607
9000	8968	1240	12156	620
9200	9166	1268	12425	634
9400	9364	1295	12693	648
9600	9562	1322	12962	662
9800	9760	1350	13230	676
10000	9958	1377	13499	690